

Project Name	Type
Catalog Number	


# OceanWalk - Round CF/HID



\*OWK-2 w/ COG



## Dimensional Drawings



\*Shown w/ Paracline Reflector      \*Shown w/ 45° Cutoff Grill

Fixture	A	B	Max. Watts	Lbs
OWK-1	6" or 8"	36" or 42"	100 W	40
OWK-2	6" or 8"	36" or 42"	100 W	40

The **OceanWalk - Round** series of architectural bollards combines contemporary styling with durable, vandal-resistant construction and smooth, low-level, 360-degree symmetrical illumination with available cutoff optics; and is an excellent choice for walkways, entrances, promenades, plazas, courtyards, driveways and landscaped areas.

**Lens:** Clear, high-impact-resistant acrylic, with silicone gasketing for a weather-tight seal. An internal light shield is available.

**Housing:** Extruded aluminum housing in 6" and 8" diameter sizes. Heavy-duty cast aluminum base plate concealed within shaft is designed for standard anchor bolt mounting to a concrete base. 3/8" x 12" galvanized anchor bolts come standard. Optional Vandal-Resistant Base available.

**Finish:** Durable Quali-Guard® textured thermoset polyester powder coat, available in a selection of architectural or custom colors. Finish is guaranteed for two (2) years.

**Optics:** Choice of specular aluminum paracline reflector, aluminum stack louver, prismatic glass refractor or 45° cutoff grill.

**Lamp:** A selection of Compact Fluorescent (26 to 42 watts) and HID light sources (50 to 100 watts) are offered; including Pulse Start Metal Halide for superior efficiency, lumen maintenance and color rendition.

**Ballast:** **HID** - Premium HPF regulating autotransformer, available in High Pressure Sodium or Pulse Start Metal Halide. **CF** - A high-performance, electronic transformer operates at 120 thru 277 volts, 50 to 60 Hz, with a 90% power factor, and is rated for -20 °C operation.

Model	Size	Optics	Wattage	Source	Voltage	Mounting	Finish	Options
OWK-1 Round Flat Top	6" Round *Specify height 36" (6R36)	Paracline Reflector (PR) 	HID 50 (50)	PS (P) HPS (S)	120 (1)	Anchor Base (AB)	Bronze (BZ)	Fusing *Specify voltage Single in-line fuse (SF120) (SF277) Double in-line fuse (DF208) (DF240) (DF480)
	42" (6R42)		70 (70)		208 (2)		Black (BK)	
OWK-2 Round Dome Top	8" Round *Specify height 36" (8R36)	Stack Louver Reflector (SLR) 	Compact Fluorescent *120-277 V Universal voltage 26 (26DT) 26x2 *COG only (26DTx2)	CF (CF)	240 (3)	M-Tap *Multi-Tap ballast wired at 277 V unless specified (6)	White (WH)	Internal Light Shield (ILS)  Emergency Battery Pack *CF only. Gives 90+ minutes of illumination during power outages. (EBP)
					277 (4)		Forest Green (FG)	
	42" (8R42)	Type V Glass Refractor (GR5) 	32 (32TT) 32x2 *COG only (32TTx2)	480 (5)	347 (8)	Silver Metallic (SL)	Cold Weather Battery Pack *CF only. Gives 90+ minutes of illumination during power outages. Rated to -20 °C. (CLDPK)	
								42 (42TT) 42x2 *COG only (42TTx2)
		45° Cutoff Grill (COG) *8" round only 						

Base Template 6" Round Bollard  
Ø 6"

Base Template 8" Round Bollard  
Ø 8"

\*Optional internal, cast-extruded Vandal-Resistant Base

For more detailed information on mounting, wiring or installation instructions, please consult factory. If poles are not ordered with fixtures, please specify mounting requirements. This document contains proprietary information of Visionaire Lighting, LLC. Any use of this information requires the written approval of Visionaire Lighting, LLC. In keeping with our TQM policy of continuous improvement, Visionaire reserves the right to change any specifications contained herein without prior notice.



19645 Rancho Way • Rancho Dominguez, CA • 90220  
Tel: (310) 512-6480 • Fax: (310) 512-6486  
www.visionairelighting.com