

OceanWalk - Round LED


Project Name	Type
Catalog Number	



*OWK-2 w/ COG



Dimensional Drawings



*Shown with Paracline Reflector *Shown with 45° Cutoff Grill

Fixture	A	B	Max. Watts	Lbs
OWK-3	8"	36" or 42"	60 W	38

The **OceanWalk - Round LED** series of architectural bollards combines contemporary styling with durable, vandal-resistant construction and smooth, low-level, 360-degree symmetrical illumination with available cutoff optics; and is an excellent choice for walkways, entrances, promenades, plazas, courtyards, driveways and landscaped areas.

Lens: Clear, high-impact-resistant acrylic, with silicone gasketing for a weather-tight seal. An internal light shield is available.

Housing: 8" diameter extruded aluminum housing. Heavy-duty cast aluminum base plate concealed within shaft is designed for standard anchor bolt mounting to a concrete base. 3/8" x 12" galvanized Anchor bolts. Optional Vandal-Resistant Base available for 8" model.

Finish: Durable Quali-Guard® textured thermoset polyester powder coat, Available in a selection of architectural or custom colors. Finish is guaranteed for two (2) years.

Optics: Choice of specular aluminum paracline reflector, Aluminum stack louver, or 45° cutoff grill provides Type V symmetrical light distribution.

Lamp: High lumen output VisionBar™ LEDs are utilized, offering a minimum estimated life of 60,000 hours.

Ballast: A high-performance LED driver operates at 120 thru 277 volts, 50 to 60 Hz, with a 90% power factor; and is rated for -40 °C operation.

Model	Size	Optics	Wattage	Source	Kelvin	Voltage	Mounting	Finish	Options
OWK-1 Round Flat Top	8" Round *Specify height 36" (8R36)	Paracline Reflector (PR) 	<u>LED</u> 20 *At 350 mA (20L)	LED (LED)	4000K (4K)	120-277 *Universal voltage (UNV)	Anchor Base (AB)	Bronze (BZ) Black (BK) White (WH) Forest Green (FG) Grey (GY) Silver Metallic (SL) Custom Color (CC)	Fusing *Specify voltage Single in-line fuse (SF120) (SF277) Double in-line fuse (DF208) (DF240) Internal Light Shield (ILS) Vandal-Resistant Base (VRB)
OWK-2 Round Dome Top	42" (8R42)	Stack Louver Reflector (SLR) 45° Cutoff Grill (COG) 	34 *At 525 mA (34L) 60 *At 700 mA (60L)				 *Optional internal, cast-extruded Vandal-Resistant Base		 Base Template 8" Round Bollard Ø 8" 3 1/2" 4 1/2" + 4 1/2" 4 1/2" Ø 5 1/2" Bolt Circle OWK-2-8R

For more detailed information on mounting, wiring or installation instructions, please consult factory. If poles are not ordered with fixtures, please specify mounting requirements. This document contains proprietary information of Visionaire Lighting, LLC. Any use of this information requires the written approval of Visionaire Lighting, LLC. In keeping with our TQM policy of continuous improvement, Visionaire reserves the right to change any specifications contained herein without prior notice.



19645 Rancho Way • Rancho Dominguez, CA • 90220
Tel: (310) 512-6480 • Fax: (310) 512-6486
www.visionairelighting.com