


# Aria - Pendant Mount LED

Project Name	Type
Catalog Number	



## Dimensional Drawings



Fixture	A	B	Max. LEDs	Lbs
ARI-1	20"	7¼"	84	17



The **Aria - Pendant Mount** is a low-profile luminaire designed to integrate easily into any architectural environment and maximizes the latest in LED technology. It is an excellent choice for indoor retail spaces, food preparation facilities and warehouse applications.

**Lens:** Each LED is covered with an injection-molded acrylic lens that provides a unique Type V distribution pattern.


**Housing:** Die cast aluminum, permanently sealed and spun aluminum top features a die cast, tool-less entry door frame with one-piece, extruded silicone gasket.

**Finish:** Durable Quali-Guard® textured thermoset polyester powder coat, oven-baked at a temperature of 400 °F to promote maximum adherence and finish hardness. Finish is guaranteed for five (5) years.

**Optics:** The **ARI-1 Pendant Mount** comes in a Type V distribution pattern and utilizes high lumen output LEDs.

**LEDs:** High lumen output VisionBar™ LEDs are utilized, offering a minimum estimated life of 60,000 hours in the desirable light color temperature of 4,000 Kelvin.

**Driver:** A high-performance electronic LED driver operates at 120 thru 277 volts, 50 to 60 Hz, with a 90% power factor; and is rated for -40 °C operation.

Model	Optics	Source	Milliamps	Kelvin	Voltage	Mounting	Finish	Options
AR1-1	Type V (T5) 	# of LEDs	mA	4000K (4K)	120-277 *Universal voltage (UNV)	Pendant Mount *Specify pendant length (PM)	Bronze (BZ)	<b>Fusing</b> *Specify voltage Single in-line fuse <b>(SF120) (SF277)</b> Double in-line fuse <b>(DF208) (DF240)</b>  Vandal-Resistant Hardware *Tamper-proof latch screw <b>(VRH)</b>
		42 (42L)	325 (3)	530 (5)	700 (7)		Black (BK)	
		84 (84L)					White (WH)	
							Grey (GY)	
							Silver Metallic (SL)	
							Custom Color (CC)	

Pair with:



Aria Area fixture.

LED - Light Emitting Diode

## LED Data Chart

# LEDs	Output mA	Nominal Watts	System Watts 120
42	350	45	46
	530	66	70
	700	90	95
84	350	90	92
	530	132	137
	700	N/A	N/A

For more detailed information on mounting, wiring or installation instructions, please consult factory. If poles are not ordered with fixtures, please specify mounting requirements. This document contains proprietary information of Visionaire Lighting, LLC. Any use of this information requires the written approval of Visionaire Lighting, LLC. In keeping with our TQM policy of continuous improvement, Visionaire reserves the right to change any specifications contained herein without prior notice.



19645 Rancho Way • Rancho Dominguez, CA • 90220  
 Tel: (310) 512-6480 • Fax: (310) 512-6486  
 www.visionairelighting.com